



CITY OF OCEANSIDE

Building Division
300 N Coast Highway
Oceanside, CA 92054
760-435-3950
www.ci.oceanside.ca.us

C & R 101

2019 California Codes

1/1/2020-12/31/2022
Effective Date

Oceanside Design Data

[Effective 1/1/20]

Informational Bulletin

The Seismic Design Category (SDC) is “D”* when using the 2019 CBC and “D₂”* when using the 2019 CRC

**[Default Value for the 2019 CBC or the 2019 CRC - for non-engineered Structures that may not require an Engineered Design or a Soils Report see Procedure PC-3 (2010 CCR) for Soil report requirements]*

The “Equivalent Basic Wind Speed” = 71 mph

[Based on a “3-second gust” value of 85 mph & 2019 CBC Figure 1609.3.1]

Exposure B: *Shall apply where “Surface Roughness B” prevails in the upwind direction for a distance of at least 2,600 ft; Or, 20 times the building height (whichever is greater...)*

“Surface Roughness B” = Urban or suburban areas, wooded areas or other terrain with numerous closely spaced obstructions having the size of single-family dwellings or larger.

Exposure C: *Shall apply for all cases where Exposures B and D do not apply.*

“Surface Roughness C” = Open spaces with scattered obstructions having heights generally less than 30 ft. This category includes flat open country...

Exposure D: *Shall apply where “Surface Roughness D” prevails in the upwind direction for a distance of at least 5,000 ft; Or, 20 times the building height (whichever is greater...) Exposure D shall extend inland from the shoreline for a distance of 600 ft or 20 times the height of the building, whichever is greater...*

“Surface Roughness D” – Flat, unobstructed areas and water surfaces...

Climate Zone #7

Design Rainfall = 1.5 inches

[Use 2019 CPC Appendix D, Table D-1]